

Position	Count	Description	Unit price
	-1	CM3-4 A-S-G-E-AQQE  <p>Product photo could vary from the actual product</p> <p>Product No.: 96806895</p> <p>CM is a compact horizontal multistage centrifugal pump, close-coupled with a: 3-phase, 208-230YY/440-480Y V, 60 HzHz. Foot mounted motor. The pump is with axial suction port and radial discharge port including a special designed mechanical shaft seal in the solution AQQE. Shaft, impellers, chambers and filling plugs are made of stainless steel. Suction and discharge are made of Stainless steel.</p> <p>The CM can also operate as a CME by connecting the motor to a CUE. Please find more information in the CUE part of Win/WebCAPS.</p> <p>Liquid: Liquid temperature range: -4 .. 248 °F</p> <p>Technical: Speed for pump data: 3480 rpm Rated flow: 16.3 US gpm Rated head: 129 ft Shaft seal: AQQE Maximum operating pressure: 232 psi Approvals on nameplate: CE,CULUS,WRAS,ACS</p> <p>Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4401 AISI 316 Impeller: Stainless steel DIN W.-Nr. 1.4401 AISI 316 Rubber: EPDM</p> <p>Installation: Maximum ambient temperature: 131 °F Maximum operating pressure: 232 psi Max pressure at stated temperature: 145 psi / 250 °F</p>	On request

Position	Count	Description	Unit price
		232 psi / 194 °F INTERNAL NPT THREAD Pump inlet: NPT 1 Pump outlet: NPT 1 Electrical data: Motor type: 71BA IE Efficiency class: IE2 Rated power - P2: 0.992 HP Main frequency: 60 Hz Rated voltage: 3 x 208-230YY/440-480Y V Service factor: 1 Rated current: 3,4-3,6/1,7-1,8 A Rated speed: 3220-3370 rpm Enclosure class (IEC 34-5): 55 Insulation class (IEC 85): F Others: Net weight: 28 lb Gross weight: 33.6 lb	

96806895 CM3-4 60 Hz

